

TECHNICAL DATA SHEET

SMART pnt POLYMERIC BONDING PRIMER

SMART pnt is a ready-to-use, ecological, polymer, water-soluble product. It ensures adhesion of subsequent layers to the substrate and evens out the absorbency of the substrate. It can be used indoors and outdoors.

| APPLICATION | TECHNICAL DATA |
|---|--|
| ▪ For applying a priming bonding layer on substrates intended for application of: screeds, self-leveling compounds, plasters, ceramic tiles, etc. Particularly recommended for polymer and polymer-mineral waterproofing membranes. | Consumption* 0,2-0,35 kg/m ² per layer |
| ▪ Creates a waterproof primer layer on floors, terraces, balconies and roofs. | Drying time* 4-6 h |
| ▪ Used on concrete, ceramic, metal, polyurethane foam and bitumen substrates covered with a mineral layer | Application temperature + 5°C to 35°C |
| | Layers 1-2 |
| | Shelf life 24 month from the date of production |
| | It meets the requirements of PN-C-81906 |

HOW TO USE

Mix well before use. Before application, clean the substrate, repair and fill cracks and holes. On very cracked roofing felt substrates, a reinforcing insert made of mesh or polyester non-woven fabric should be used.

SMART pnt is applied with a roller, brush, brush or by spraying after mixing the product. Applying the next layer should begin when the primed surface is dry. Protect the coatings against rain and frost until they dry. Work should be carried out at temperatures from +5°C to +35°C.

*depending on external conditions.



SAFETY AND STORAGE AND TRANSPORT

- Keep away from children. In case of contact with eyes, rinse with plenty of water.
- The product should be transported and stored in tightly closed packaging at a positive temperature. Protect against overheating and frost. The shelf life of the product is 12 months from the production date indicated on the packaging.



All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.