

TECHNICAL DATA SHEET

SMART interier

Anti-condensation paint

Resistant to moisture

- Absorbs moisture
- For wet rooms
- Good coverage
- Delicate structure

- Inwards
- Ecological
- Resistant to detergents
- Resistant to mold fungi

APPLICATION

SMART interier is a paint that creates a coating that protects against surface condensation condensation of water vapor on the walls. Suitable for application on all traditional plasters (cement-lime, gypsum), concrete, plasterboards, smoothes well-adhering layers of mineral and dispersion paints. To inwards uses.

HOW TO USE

STEP 1 SUBSTRATE PREPARATION. Depending on the absorbency and type of the substrate, it should be primed. Symptoms of biological aggression should be eliminated. Repair any defects, irregularities or cracks with a material appropriate to the type of substrate. Mortars in repaired places they must be dry and well bonded. Cover surfaces not intended for painting before applying primers. It is required that the surface is dry before painting

STEP 2 PRODUCT PREPARATION. The product is ready for use. Do not dilute with water or mix with other materials. Before use, mix the contents of the package thoroughly.

STEP 3 USING. Apply the paint with a brush or roller.

NOTES

- The substrates must be cleaned of dust, grease, release agents, paint residues, mold, algae, mosses, etc., free from cracks and salt efflorescence.
- Ventilate the room while working and drying, but protect against drafts causing it to dry too quickly.
- Paint continuously on one surface, not allowing any part of the paint to dry to avoid visible joints
- Apply the next layer of paint after the previous one has dried for at least 6 hours.

SAFETY AND STORAGE AND TRANSPORT

- Keep away from children. In case of contact with eyes, rinse with plenty of waters.
- The product should be transported and stored in tightly closed packaging at a positive temperature. Protect against overheating and frost. The shelf life of the product is 12 months from the production date indicated on the packaging.

TECHNICAL DATA

Consumption*	0,15 l/m ²
Drying time*	ok. 12h
Application temperature	+ 5°C to 25°C
Layers	1-2
Shelf life	12 month from the date of production
Colour	white
Gloss level	mat
Resistance to wet scrubbing	Class 2

*depending on external conditions.

